



- **Limit switch with snap action**
Inverseur fin de course à rupture brusque
- **Possibility of attack with a 20° cam**
Possibilité d'attaque avec une came 20° d'angle
- **Contact arrangement** **1 PDT**
Combinaison des contacts

GENERAL CHARACTERISTICS

CARACTERISTIQUES GENERALES

- **Nickel plated brass body set**
Ensemble corps laiton nickelé
- **Threaded body $\varnothing 10 \times 0.75$ for control adjustment**
Corps fileté $\varnothing 10 \times 0.75$ permettant le réglage de la commande
- **Weight** **15 g $\pm 5\%$**
Masse

ELECTRICAL CHARACTERISTICS

CARACTERISTIQUES ELECTRIQUES

| Circuit <i>Circuits</i> | 30 Vcc | 115 V / 400 Hz |
|---|-------------------|----------------|
| Resistive / Résistif | 3 A | 2 A |
| Inductive 5/1000 / Inductif (5/1000) | 2 A | 1.5 A |
| Lights / Lampes | 1.5 A | 1 A |
| Voltage drop at 3A / Chute de tension à 3A | 60 mV max | |
| Temperature range / Gamme de température | -50°C to +80°C | |
| Endurance / Endurance | 50 000 operations | |

LEACH INTERNATIONAL EUROPE S.A.S.
 Tel: +33 3 87 97 98 97
 Fax: +33 3 87 97 96 86

LEACH INTERNATIONAL ASIA PACIFIC
 Tel: +852 2 191 3830
 Fax: +852 2 389 5803

The technical information provided by Leach International Europe is to be used as a guide only, and is not meant for publication or as documentation for altering any existing specification. Dimensions are in millimeters unless otherwise specified. Rev. 03/2025.

MECHANICAL CHARACTERISTICS CARACTERISTIQUES MECANIKUES

| Forces / Forces | |
|--|----------------|
| Operating / Commande | 1.5 kg max |
| Release / Relâchement | 0.4 kg min |
| End of travel / Fin de course | 4 kg max |
| Tightening torque / Couple de serrage | 50 to 60 cm.kg |
| Operating travel / Course de commande | 1.8 mm max |
| Max total travel / Course totale maxi | 4 mm |
| Release travel / Course de relâchement | 1 mm max |

MOUNTING STYLES TYPES DE CONFIGURATION

Dimensions are in mm
 General tolerances, ± 0.3 mm

